



**TigerTurf™**  
**ENDURANCE**




**TigerTurf Endurance is constructed with XPS, the world's most durable slit film fibers, and has exceptional strength.**

Created on the only two machines of their kind in the world, our XPS fibers consistently retain their character for longer, harder games. Our resilient XPS yarn reduces infill movement and creates surface stability while offering the longest life cycle of any fiber in the world.

**TURF**

**PILE CONTENT**



Tencate U.V. resistant XPS Plus

HIGH SPLIT RESISTANCE FROM UNIQUELY ENGINEERED SLIT FILM DESIGN

<b>PRIMARY BACKING</b>	7.5 oz/yd <sup>2</sup> ; TenCate K29 Backing (Double Layer Thiobac, black, U.V. stabilized; Layer 1: 100% PP, Layer 2: PET/PP blend)
<b>SECONDARY BACKING</b>	20 oz/yd <sup>2</sup> ; Polyurethane coating with drainage holes
<b>TOTAL WEIGHT</b>	72.5 oz/yd <sup>2</sup>
<b>PILE HEIGHT</b>	1 3/4 inch or 2 inch
<b>FACE WEIGHT*</b>	45 oz/yd <sup>2</sup>
<b>MACHINE GAUGE</b>	1/2 inch
<b>SET UP</b>	1 end/needle
<b>ROLL WIDTH</b>	182 inch
<b>WATER PERMEABILITY</b>	> 50 inches/hour
<b>TUFT BIND (ASTM D1335)</b>	≥ 8 lbs
<b>GRAB TEAR (ASTM D5034)</b>	250/250 lbs
<b>PILL FLAMMABILITY (ASTM D2859)</b>	Pass



BEST FOR MULTI-SPORT, BASEBALL, SOFTBALL

**MADE IN THE USA**

**TENCATE GRASS**

**YARN**

<b>DENSITY (DENIER)</b>	10,000/1
<b>THICKNESS (MICRONS)</b>	120
<b>MELTING POINT</b>	128° C   260°F
<b>BREAKING STRENGTH</b>	24 lbs/force
<b>LEAD CONTENT (PPM)</b>	<100

**STANDARD COLORS**

 <b>FIELD GREEN</b> Pantone: 575C	 <b>LIME GREEN</b> Pantone: 7496C	 <b>FIELD GREEN/ LIME GREEN</b>
 <b>BROWN</b> Pantone: 1545C	 <b>NAVY BLUE</b> Pantone: 282C	 <b>FLORIDA BLUE</b> Pantone: 281C
 <b>GRAY</b> Pantone: 422+429	 <b>BLACK</b> Pantone: 000C	 <b>RED</b> Pantone: 185C
 <b>ORANGE</b> Pantone: 166C	 <b>BLUE LAGOON</b> Pantone: 2925C	 <b>RED CLAY</b> Pantone: 7526C
 <b>CRIMSON</b> Pantone: 202C	 <b>BLUPLE</b> Pantone: 268C	 <b>TAN</b> Pantone: 728C
 <b>BRIGHT YELLOW</b> Pantone: 136C	 <b>WHITE</b> Pantone: 000	 <b>VEGAS GOLD</b> Pantone: 466C

Pile Height, Max Thickness, Face Weight, Primary & Secondary Backing, and Total Weight can differ by ±10%. The Stitch Rate will change according to the exact specifications and can differ by ±1. Roll Width can differ by ±0.8 inch.

TenCate Grass has the right to alter each product specification in order to improve the system according to the latest standards. TenCate Grass is not legally liable in case of noncompliance with the above mentioned specifications.

\*Face Weight reflects entire length of yarn, including portion woven into backing, which is consistent with standard ASTM method of measuring tuft including back stitch.